

MAXXIMUM PERFORMANCE™ LUBRICANTS



SYNTHETIC GEAR OILS

Maxximum Performance™ Synthetic Gear Oils are heavy duty, extreme pressure, GL-5 synthetic gear lubricants. Engineered with state-of-the-art advanced additive chemistry which includes extreme pressure, as well as rust, oxidation, and corrosion inhibitors. Designed to provide supreme protection of gears and bearings operating under a wide variety of load conditions and temperatures.

Performance Features

- Extreme pressure properties to minimize wear
- Protects against Micropitting
- Outstanding rust protection
- Dissipates heat quickly
- Excellent antifoam and demulsification Properties
- Non-corrosive to bronze and bearing alloys

Approvals

75W-85

- API GL-5
- API MT-1
- MIL-L-2105E
- GM 88862826
- Chrysler/Dodge/Jeep
- Toyota/Lexus Gear Oil LT
- MB235.15/235.7/235.74
- BMW 83 12 0 445 868/
BOT 448
- AUDI G052 513

75W-90

- API GL-5
- API MT-1
- MIL-PRF 2105E
- MIL-L-2105D
- J2360
- Mack GO-J Plus
- Meritor O-76N
Extended Drain
- MAN 342 Type M2

75W-140

- API GL-5
- API MT-1
- MIL-PRF-2105E
- MIL-L-2105D
- J2360
- Mack GO-J

Available in: 12x1 Quart cases, 6 Gallon Bag in Boxes (22.68 Liters), 5 Gallon pails, 16 Gallon kegs, 55 Gallon drums, & bulk