

Safety Data Sheet

Conventional 10W-40 API SP

1. IDENTIFICATION

Product Identification

Product Name: Maxximum Performance Conventional 10W-40 API SP Product Number: 01172001 Recommended Use: Engine Oil

Company Identification

Reliance Fluid Technologies, LLC 3943 Buffalo Ave. Niagara Falls, New York, 14303 1-716-332-0988 (For product information) 1-716-332-0988 (For emergencies) 1-800-424-9300 or 1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

OSHA/HCS STATUS:

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

CLASSIFICATION(S):

Not Classified

SIGNAL WORD:

No Signal Word.

SYMBOL(S):

HAZARD STATEMENT(S):

No known significant effects or critical hazards.

PRECAUTIONARY STATEMENT(S):

GENERAL PRECAUTIONARY STATEMENT(S):

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

| Hazard Rating | | |
|----------------------|------|--|
| | HMIS | |
| Health: | 1 | |
| Flammability: | 1 | |
| Reactivity: | 0 | |
| Personal Protection: | В | |



PREVENTION PRECAUTIONARY STATEMENT(S): Not applicable.

RESPONSE PRECAUTIONARY STATEMENT(S):

Not applicable.

STORAGE PRECAUTIONARY STATEMENT(S):

Store in a dry place. Store in a closed container.

DISPOSAL PRECAUTIONARY STATEMENT(S):

Dispose of contents/containers should be cleaned of residual product before disposal, and disposed of in accordance with all applicable laws and regulations.

OTHER HAZARDS WHICH DO NOT RESULT IN CLASSIFICATION: No additional information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT LISTING:

| Ingredient Name | Amount | CAS Number |
|-----------------------------------|----------|-------------|
| Highly Refined Petroleum Base Oil | 80 - 92% | Mixture |
| Additives | < 20% | Proprietary |

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SKIN CONTACT FIRST AID:

Wash skin with plenty of soap and water while removing contaminated clothing and shoes.

INHALATION FIRST AID:

IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

INGESTION FIRST AID:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

NOTES TO PHYSICIAN:

Treat Symptomatically.



5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

PMCC Flash Point: 205 °C (401 °F) Autoignition Temperature: N/A

FLAMMABLE LIMITS IN AIR

LEL: N/A UEL: N/A

EXTINGUISHING MEDIA:

Carbon dioxide, foam, or dry powder. Do not use water, because this product is oil based. Water may cause frothing.

FIRE & EXPLOSION HAZARDS:

Can burn in fire, releasing toxic vapors, fumes, and smoke.

FIRE FIGHTING INSTRUCTIONS:

As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

COMBUSTION PRODUCTS:

Hazardous decomposition products are oxides of carbon and nitrogen including CO and CO2.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):

Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

INITIAL CONTAINMENT:

Absorb spills with inert material. Do not allow material to enter soil or surface water.

LARGE SPILLS PROCEDURE:

Absorb spill with inert material (e g, dry sand or earth), then place in a chemical waste container. Do not flush to sewer.

SMALL SPILLS PROCEDURE:

Absorb spills with inert material.

MISCELLANEOUS:

Treat or dispose of in accordance with all federal, state, and local requirements. Incineration is preferred.



7. HANDLING AND STORAGE

HANDLING (PERSONNEL):

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner, or properly disposed of. Wash hands thoroughly after handling.

HANDLING (PHYSICAL ASPECTS):

Secure container after each use. Store in a cool dry area.

Avoid contact with strong oxidizing agents.

STORAGE PRECAUTIONS:

Store in a cool dry place, in a tightly closed container. Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| Material | Source | Туре | mg/m3 |
|----------------------------|-----------|--------------------------|----------|
| Lubricating Oil, Petroleum | NIOSH REL | TWA (Mist.) | 5 mg/m3 |
| Lubricating Oil, Petroleum | NIOSH REL | STEL (Mist.) | 10 mg/m3 |
| Highly Refined Base Oil | ACGIH TLV | TWA (Inhalable fraction) | 5 mg/m3 |
| Highly Refined Base Oil | NIOSH REL | TWA | 5 mg/m3 |

OCCUPATIONAL EXPOSURE LIMITS

ENGINEERING CONTROLS:

Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. TLV for mineral oil is 5 mg/cubic meter.

EYE / FACE PROTECTION REQUIREMENTS:

When splashing of the material may occur, chemical goggles and/or a face shield are recommended.

SKIN PROTECTION REQUIREMENTS:

Where contact is likely, wear chemical resistant gloves.

RESPIRATORY PROTECTION REQUIREMENTS:

Under normal use conditions, with adequate ventilation, no special handling equipment is required. If mists are produced, local ventilation may be required to keep exposure below limits.

GENERAL COMMENTS:

Always observe good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, etc...



9. PHYSICAL AND CHEMICAL PROPERTIES

| FORM | Liquid |
|---------------------|---------------------------------|
| COLOR | Amber |
| ODOR | Petroleum |
| VAPOR DENSITY | Heavier than air (Air = 1) |
| SOLUBILITY IN WATER | Nil |
| SPECIFIC GRAVITY: | 0.8608 at 60 °F (Water = 1) |
| BULK DENSITY | 7.17 Pounds per Gallon at 60 °F |
| MELTING PT | : N/D |
| рН | Not applicable |
| VISCOSITY | 15.74 cSt at 100 °C |
| | |

10. STABILITY AND REACTIVITY

STABILITY:

Stable.

POLYMERIZATION:

Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:

Avoid contact with strong oxidizing agents.

DECOMPOSITION:

In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced. Hydrogen sulfide and alkyl mercaptans and sulfides may also be released.

11. TOXICOLOGICAL INFORMATION

GENERAL INFORMATION:

Based on data on the components and the toxicology of similar materials

ROUTES OF ENTRY:

Skin, Eyes, Ingestion, and Inhalation.

ACUTE EXPOSURE:

EYE IRRATATION:

Not expected to cause eye irritation. Based on data from components or similar materials. Vapors may cause irritation.

SKIN IRRATATION:

Slightly irritating based on data from components or similar materials. Prolonged or repeated skin contact without proper hygiene may result in skin disorders such as acne.

RESPIRATORY IRRITATION:

Based on data from components and similar materials, Inhalation of vapors or mists may cause irritation.



DERMAL TOXICITY:

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rabbit

ORAL TOXICITY:

Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat

INHALATION TOXICITY:

Based on data from components and similar materials, product is not considered to be an inhalation hazard under normal conditions of use.

SENSITISATION:

Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components or similar formulations.

CHRONIC EXPOSURE:

CHRONIC TOXICITY:

No data available to indicate product or components present at greater than 1% are chronic health hazards.

CARCINOGENICITY:

Product contains mineral and/or synthetic oils shown to be noncarcinogenic in laboratory studies with the same or similar materials. Mineral and synthetic oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.

MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

REPRODUCTIVE TOXICITY:

No data available to indicate either product or components present at greater than 0.1% that may cause reproductive toxicity.

TERATOGENCITY:

No data available to indicate either product or components present at greater than 0.1% that may cause birth defects.

ADDITIONAL INFORMATION:

No other health hazards known.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS:

Ecological Toxicity data has not been determined specifically for this product. The ecological toxicity hazard is based on an evaluation of data for the components or a similar material. This material is expected to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

ENVIRONMENTAL FATE

This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. This product contains components which may be persistent in the environment.



13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Avoid disposal into waste water treatment facilities. Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements. This product, if discarded, is not considered a hazardous waste.

14. TRANSPORTATION INFORMATION

PRODUCT LABEL: Maxximum Performance Conventional 10W-40 API SP D.O.T SHIPPING: Not Regulated by DOT. IMDG: This material is not classified as dangerous under IMDG regulations. IATA: This material is not classified as dangerous under IATA regulations. TRANSPORT CANADA: This material is not classified as dangerous under Transport Canada regulations.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard:

The classification of this material is based on OSHA HCS 2012 criteria.

| United States inventory (TSCA): | All | components | are | listed | or | exempted. |
|---------------------------------|-----|------------|-----|--------|----|-----------|
| Canada inventory: | All | components | are | listed | or | exempted. |
| Europe inventory: | All | components | are | listed | or | exempted. |
| Japan inventory (ENCS): | All | components | are | listed | or | exempted. |
| Australia inventory (AICS): | All | components | are | listed | or | exempted. |
| Korea inventory (KECI): | All | components | are | listed | or | exempted. |
| China inventory (IECSC): | All | components | are | listed | or | exempted. |
| Philippines inventory (PICCS): | All | components | are | listed | or | exempted. |

16. OTHER INFORMATION

| REASON FOR ISSUE: | New |
|-------------------|--------------------------|
| APPROVAL DATE: | May 1, 2020 |
| SUPERCEDES DATE: | New |
| RTN NUMBER | 01172001 (Official Copy) |

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Reliance Fluid Technologies, LLC. The data on this sheet are related only to the specific material designated herein. Reliance Fluid Technologies, LLC assumes no legal responsibility for use or reliance upon these data.